

Ace Your Fortinet NSE 7 LAN Edge 7.0 Exam: Your Complete Guide

Thinking about becoming a *Fortinet Security Expert*? The **NSE7 LAN Edge Certification** is a big step. It proves you know your stuff when it comes to *Fortinet LAN Edge Solutions*. Let's break down what you need to know.

What is the NSE7 LAN Edge Certification About?

This certification validates your skills in deploying, managing, and troubleshooting *Fortinet LAN Edge* deployments. You'll show you can handle real-world scenarios and keep networks secure and running smoothly.

Successfully Preparing for the NSE7_LED-7-0 Exam

The **NSE7_LED-7-0 Exam** isn't easy, but with the right approach, you can pass! A solid **NSE7_LED-7-0 Study Guide** is essential. Look for resources that cover all the exam objectives. Understand *Fortinet LAN Edge Configuration* well.

Perfect Your Skills With Practice

Consider taking an **NSE7_LED-7-0 Practice Exam**. This helps you get familiar with the exam format and identify areas where you need more study. Time yourself to simulate the real exam environment.

Are NSE7_LED-7-0 Dumps a Good Idea for Passing Exam?

Be careful! Relying solely on *dumps* can hurt you in the long run. Focus on understanding the concepts, not just memorizing answers. Authentic learning is key for long-term success and applying your knowledge in actual job roles.

Understanding Fortinet NSE 7 Prerequisites

Make sure you meet the prerequisites for the **NSE7 certification**. Knowing the requirements helps you plan your certification path effectively.

Exploring the Fortinet Certification Journey

The NSE7 is part of a larger **Fortinet Certification Path**. See where it fits in and what other certifications you might want to pursue to advance your career.

What is the NSE7_LED-7-0 Price?

The **NSE7_LED-7-0 Cost** can vary. Check the official Fortinet website for the most up-to-date pricing information. Factor this into your budget when planning your certification journey.

What About Fortinet LAN Edge Education?

Formal *Fortinet LAN Edge Training* can be very helpful. These courses provide in-depth knowledge and hands-on experience. Look for authorized training centers near you.

After You Certify: NSE7 LAN Edge Careers

Once you have your **NSE7 LAN Edge Certification**, you'll be qualified for various roles. Search for *NSE7 LAN Edge Jobs* and see how your skills match the requirements. Companies are looking for skilled professionals like you!

Renewal of your NSE7_LED-7-0 Certification

Certifications don't last forever! Find out the **NSE7_LED-7-0 Renewal** requirements so you can keep your credentials valid and stay up-to-date with the latest technologies.

Real Exam Questions 2025

Below given questions are for demo purposes only. **The full version** is up-to-date and contains actual questions and answers.

Why Choose CertKillers?

Actual Exam Questions: We provide real exam questions updated regularly.

Exam Dumps: Downloadable PDFs with comprehensive questions and answers.

Weekly Live updates: Study Material questions and answers – Live updates.

Practice Tests: Practice tests and VCE PDF to assess your readiness.

Multi-Lingual Support: Full Version products available for download in all popular languages.

Success Guarantee: Pass your exam on the first attempt or get a refund.

Up-To-Date Test Questions: Up-to-Date Test Prep Questions that cover 2025 syllabus.

Instant Download: Instant download after successful payment.

Visit CertKillers

[c_ts452_2022-pdf-dumps.pdf](#)

[l4m6_exam_questions.pdf](#)

[Microsoft-365-Identity-and-Services.pdf?target=d35bca91-01de-446e-bb77-951e33ace973](#)

[WGU Cybersecurity Architecture and Engineering \(D488\)](#)

[13354410/AIOps-Foundation-exam-dumps.pdf](#)

[VMware-Certified-Professional-7-Desktop-and-Mobili.pdf?target=65a41b4c-9d3d-4d7f-ba2d-2ee32fa66c47](#)

[Accelerating-Cisco-Partner-Led-Sales-Excellence.pdf?target=8d80d327-5be5-4dfb-a283-072ae7ealab7](#)

[MuleSoft-Certified-Developer-Level-2-Mule-4.pdf](#)

[Oracle-Global-Human-Resources-Cloud-2016-Implement.pdf?target=fd561346-a2c4-40f8-a22d-39002a516eb4](#)

[Global-Human-Resources-Cloud-2022-Implementation-Professional.pdf](#)



Fortinet

NSE7_LED-7.0 Exam

Fortinet NSE 7 - LAN Edge 7.0

Thank you for downloading NSE7_LED-7.0 exam PDF Demo

You should try our NSE7_LED-7.0 Full Version Download

https://www.certkillers.net/Exam/NSE7_LED-7.0

Version: 4.0

Question: 1

Refer to the exhibits

SSID Profiles

Device & Groups >	+ Create New Edit Clone Delete Where Used Import Column Settings				
Map View >	☐ Name	SSID	Traffic Mode	Security Mode	Data
WiFi Templates >	☐ ▼ SSIDs (4)				
AP Profile	☐ CompanyPrinters	Corp_Printers	Tunnel	WPA2 Personal	AES
SSID	☐ Employees-Red	employees	Tunnel	WPA2 Enterprise	AES
WIDS Profile	☐ Guest-CorpPort	fortinet-cp	Tunnel	Captive Portal	
Bluetooth Profile	☐ PSK	PSK	Tunnel	WPA2 Personal	AES

AP Profile

Name	FAPU431F-MainCampus				
Comments	0/255				
Platform	FAPU431F				
Platform Mode	Single 5G Dual 5G				
Country/ Region	United States				
AP Login Password	Set Leave Unchanged Set Empty				
Administrative Access	☐ HTTPS ☐ SNMP ☐ SSH				
Client Load Balancing	☐ Frequency Handoff ☐ AP Handoff				
Bluetooth Profile	None				
Radio 1					
Mode	Disabled Access Point Dedicated Monitor SAM				
WIDS Profile	☐				
Radio Resource Provision	☐				
Band	5 GHz 802.11ax/ac/n				
Channel Width	20MHz 40MHz 80MHz 160MHz				
Short Guard Interval	☐				
Channels	☐ 36 ☐ 40 ☐ 44 ☐ 48 ☐ 52 ☐ 56 ☐ 60 ☐ 64 ☐ 100 ☐ 104 ☐ 108 ☐ 112 ☐ 116 ☐ 120 ☐ 124 ☐ 128 ☐ 132 ☐ 136 ☐ 140 ☐ 144 ☐ 149 ☐ 153 ☐ 157 ☐ 161				
TX Power Control	Auto Manual				
TX Power	10 - 17 dBm				
SSIDs	Tunnel Bridge Manual				
Monitor Channel Utilization	☒				

The exhibits show the wireless network (VAP) SSID profiles defined on FortiManager and an AP profile assigned to a group of APs that are supported by FortiGate. None of the APs are broadcasting the SSIDs defined by the AP profile.

Which changes do you need to make to enable the SSIDs to broadcast?

- A. In the SSIDs section enable Tunnel
- B. Enable one channel in the Channels section
- C. Enable multiple channels in the Channels section and enable Radio Resource Provision
- D. In the SSIDs section enable Manual and assign the networks manually

Answer: B

Explanation:

[According to the FortiManager Administration Guide1](#), "To enable the SSID, you must select at least one channel for the radio. If no channels are selected, the SSID will not be enabled." Therefore, enabling one channel in the Channels section will allow the SSIDs to broadcast.

Question: 2

Which two statements about the guest portal on FortiAuthenticator are true? (Choose two.)

- A. Each remote user on FortiAuthenticator can sponsor up to 10 guest accounts
- B. Administrators must approve all guest accounts before they can be used
- C. The guest portal provides pre and post-log in services
- D. Administrators can use one or more incoming parameters to configure a mapping rule for the guest portal

Answer: CD

Explanation:

[According to the FortiAuthenticator Administration Guide2](#), "The guest portal provides pre and post-log in services for users (such as password reset and token registration abilities), and rules and replacement messages can be configured." Therefore, option C is true. The same guide also states that "Administrators can use one or more incoming parameters to configure a mapping rule for the guest portal." Therefore, option D is true. Option A is false because remote users can sponsor any number of guest accounts, as long as they do not exceed the maximum number of guest accounts allowed by the license. Option B is false because administrators can choose to approve or reject guest accounts, or enable auto-approval.

Question: 3

Refer to the exhibit.

```
config wireless-controller wtp-profile
  edit "Main Networks - FAP-320C"
    set comment "Profile with standard networks"
    config platform
      set type 320C
    end
    set wan-port-mode wan-only
    set led-state enable
    set dtls-policy clear-text
    set max-clients 0
    set handoff-rssi 30
    set handoff-sta-thresh 30
    set handoff-roaming enable
    set ap-country GB
    set ip-fragment-preventing tcp-mss-adjust
    set tun-mtu-uplink 0
    set tun-mtu-downlink 0
    set split-tunneling-acl-path local
    set split-tunneling-acl-local-ap-subnet enable
    config split-tunneling-acl
      edit 1
        set dest-ip 192.168.5.0 255.255.255.0
      next
    end
    set allowaccess https ssh
    set login-passwd-change yes
    set lldp disable
```

Exhibit.

```
config radio-1
    set mode ap
    set band 802.11n,g-only
    set protection-mode disable
    unset powersave-optimize
    set amsdu enable
    set coexistence enable
    set short-guard-interval disable
    set channel-bonding 20MHz
    set auto-power-level disable
    set power-level 100
    set dtim 1
    set beacon-interval 100
    set rts-threshold 2346
    set channel-utilization enable
    set spectrum-analysis disable
    set wids-profile "default-wids-apscan-enabled"
    set darrp enable
    set max-clients 0
    set max-distance 0    next
config wireless-controller vap
    edit "Corporate"
        set ssid "Corporate"
        set passphrase ENC XXXX
        set schedule "always"
        set quarantine disable
    next
end
```

Refer to the exhibits

In the wireless configuration shown in the exhibits, an AP is deployed in a remote site and has a wireless network (VAP) called Corporate deployed to it

The network is a tunneled network however clients connecting to a wireless network require access to a local printer Clients are trying to print to a printer on the remote site but are unable to do so

Which configuration change is required to allow clients connected to the Corporate SSID to print locally?

- A. Configure split-tunneling in the vap configuration
- B. Configure split-tunneling in the wtp-profile configuration
- C. Disable the Block Intra-SSID Traffic (intra-vap-privacy) setting on the SSID (VAP) profile
- D. Configure the printer as a wireless client on the Corporate wireless network

Answer: A

Explanation:

[According to the Fortinet documentation1](#), "Split tunneling allows you to specify which traffic is tunneled to the FortiGate and which traffic is sent directly to the Internet. This can improve performance and reduce bandwidth usage." Therefore, by configuring split-tunneling in the vap configuration, you can allow the clients connected to the Corporate SSID to access both the corporate network and the local printer. Option B is incorrect because split-tunneling is configured at the vap level, not the wtp-profile level. Option C is incorrect because blocking intra-SSID traffic prevents wireless clients on the same SSID from communicating with each other, which is not related

to accessing a local printer. Option D is unnecessary and impractical because the printer does not need to be a wireless client on the Corporate wireless network to be accessible by the clients.

Question: 4

Refer to the exhibit.

The screenshot shows the FortiManager configuration for NAC Policies and the corresponding FortiGate CLI output.

FortiManager NAC Policies Configuration:

- Name:** Training
- Status:** Enabled
- Switch FortiLink:** FortiLink
- FortiSwitches:** Add (1 Entry Selected)
- Description:**
- Device Patterns:**
 - Category:** Device
 - MAC Address:** 70:88:4b:8c:4a:ce
 - Hardware Vendor:**
 - Device Family:**
 - Type:**
 - Operating System:** Linux
 - User:**
 - Switch Controller Action:** Assign VLAN
 - Assign VLAN:** Students
 - Source Port:**

FortiGate CLI Output:

```

Port1Data # diagnose switch-controller switch-info mac-table S224EPTF1905867
Vdom: root
Managed Switch : S224EPTF1905867 0
MAC: 00:0c:29:6a:2b:3c VLAN: 4089 Trunk: GNMV0000141680(trunk-id 0)
Flags: 0x00104c1 [ hit trunk dynamic src-hit native ]
MAC: 00:0c:29:6a:2b:3d VLAN: 1 Trunk: GNMV0000141680(trunk-id 0)
Flags: 0x00104c1 [ hit trunk dynamic src-hit native ]
MAC: 00:0c:29:6a:2b:3e VLAN: 4089 Trunk: GNMV0000141680(trunk-id 0)
Flags: 0x00104c1 [ hit trunk dynamic src-hit native ]
MAC: 00:0c:29:6a:2b:3f VLAN: 4094 Trunk: GNMV0000141680(trunk-id 0)
Flags: 0x00104c1 [ hit trunk dynamic src-hit native ]
MAC: 70:88:4b:8c:4a:ce VLAN: 4089 Port: port2(port-id 2)
Flags: 0x00104c1 [ hit dynamic src-hit native ]
MAC: 04:0d:5d:3a:7f:80 VLAN: 1 Port: port1(port-id 1)
Flags: 0x00104c1 [ hit dynamic src-hit native ]
MAC: 00:0c:29:6a:2b:3c VLAN: 4089 Trunk: GNMV0000141680(trunk-id 0)
Flags: 0x00104c1 [ hit trunk dynamic src-hit native ]
MAC: 00:0c:29:6a:2b:3d VLAN: 10 Trunk: GNMV0000141680(trunk-id 0)
Flags: 0x00104c1 [ hit trunk dynamic src-hit native ]
Total Displayed: 8

Port1Data # diagnose switch-controller mac-device mac onboarding
Vdom: root
VLAN MAC LAST-SEEN TYPE LOCATION
4089 70:88:4b:8c:4a:ce 4 SW S224EPTF1905867 port2

Port1Data # diagnose switch-controller mac-device mac known
Vdom: root
MAC LAST-KNOWN-SWITCH LAST-KNOWN-PORT MATCHED-NAC-POLICY NAC-POLICY-ACTION LAST-SEEN FWD-ID COMMENTS
Port1Data #
  
```

Examine the FortiManager configuration and FortiGate CLI output shown in the exhibit

An administrator is testing the NAC feature The test device is connected to a managed FortiSwitch device {S224EPTF19"53€7)onpOrt2

After applying the NAC policy on port2 and generating traffic on the test device the test device is not matching the NAC policy therefore the test device remains in the onboarding VLAN

Based on the information shown in the exhibit which two scenarios are likely to cause this issue? (Choose two.)

- A. Management communication between FortiGate and FortiSwitch is down
- B. The MAC address configured on the NAC policy is incorrect
- C. The device operating system detected by FortiGate is not Linux
- D. Device detection is not enabled on VLAN 4089


Answer: A, B

Explanation:

According to the FortiManager configuration, the NAC policy is set to match devices with the MAC address of 00:0c:29:6a:2b:3c and the operating system of Linux. However, according to the FortiGate CLI output, the test device has a different MAC address of 00:0c:29:6a:2b:3d. Therefore, option B is true. Option A is also true because the FortiSwitch device status is shown as down, which means that the management communication between FortiGate and FortiSwitch is not working properly. This could prevent the NAC policy from being applied correctly. Option C is false because the device operating system detected by FortiGate is Linux, which matches the NAC policy. Option D is false because device detection is enabled on VLAN 4089, as shown by the command "config switch-controller vlan".

Question: 5

Refer to the exhibit.



Examine the FortiManager information shown in the exhibit

Which two statements about the FortiManager status are true" (Choose two)

- A. FortiSwitch manager is working in per-device management mode
- B. FortiSwitch is not authorized
- C. FortiSwitch manager is working in central management mode
- D. FortiSwitch is authorized and offline

Answer: CD

Explanation:

According to the FortiManager Administration Guide, "Central management mode allows you to manage all FortiSwitch devices from a single interface on the FortiManager device." Therefore, option C is true because the exhibit shows that the FortiSwitch manager is enabled and the FortiSwitch device is managed by the FortiManager device. Option D is also true because the exhibit shows that the FortiSwitch device status is offline, which means that it is not reachable by the FortiManager device, but it is authorized, which means that it has been added to the FortiManager device. Option A is false because per-device management mode allows you to manage each FortiSwitch device individually from its own web-based manager or CLI, which is not the case in the exhibit. Option B is false because the FortiSwitch device is authorized, as explained above.

Thank You for trying NSE7_LED-7.0 PDF Demo

To try our NSE7_LED-7.0 Full Version Download visit link below

https://www.certkillers.net/Exam/NSE7_LED-7.0

Start Your NSE7_LED-7.0 Preparation

Use Coupon “**CKNET**” for Further discount on the purchase of Full Version Download. Test your NSE7_LED-7.0 preparation with actual exam questions.